

MODEL OPTIONS

There are two Thermador Built-in Microwaves to choose from — traditional and convection. 27-inch and 30-inch stainless steel trim kits are available for each. You can also choose a Thermador Built-in MicroDrawer[™]. This product is available Q2 2012. Log on to thermador.com or visit your local dealer for planning information.

INSTALLATION CONSIDERATIONS (MBES/MCES MODELS)

The information in this design guide provides key features, product dimensions, cutouts and installation specifications. Before installing a Thermador Microwave oven, be sure to verify the cabinet dimensions and electrical connections. Also, always consult the installation manual packed with the product for complete details before installing.

It is the responsibility of the owner and the installer to determine if additional requirements and/or standards apply to specific installations.

MBES/MCES models must be used in conjunction with a 27-inch or 30-inch microwave trim kit.

The microwave oven can be installed into a cabinet or wall by itself, or above any Thermador Built-in Oven.

To reduce the risk of fire and electric shock, install microwave at least $^{3}\!/\!_{4}$ " above designated oven.

Do not block air vents. If they are blocked during operation, the oven may be overheated and damaged. If the oven overheats, a thermal safety device will turn the oven off. The oven will remain inoperable until it has cooled.

Do not place the microwave near a hot, damp surface such as a gas or electric range, dishwasher, or in an excessively humid room.

2-YEAR WARRANTY

Limited warranty parts and labor (2 year).

See page 308 for additional warranty details.

Microwaves are UL approved.

WARRANTY

ELECTRICAL SPECIFICATIONS

The microwave oven must be on a separate circuit. No other appliance should share the circuit with the microwave oven. If it does, the branch circuit fuse may blow or the circuit breaker may trip, or the food may cook slower than recommended.

This appliance must be grounded. It is equipped with a cord having a grounding wire with a grounding plug. The plug must be plugged into at least a 20 Amp, 120 Volt, 60 Hz 3-wire, grounded outlet that is properly installed.

The voltage used must be the same as specified on this microwave oven (120V, 60Hz). Using a higher voltage is dangerous and may result in a fire or oven damage. Using a lower voltage will cause slow cooking.


Do not use an extension cord. If the power supply cord is too short, have a qualified electrician or serviceman install an outlet near the appliance.

MODEL	REQUIRED CIRCUIT BREAKER
	240V, 60 Hz
MBES	20 Amp
MCES	20 Amp
MD24JS	15 Amp


ELECTRICAL LOCATION (MBES/MCES MODELS)

The outlet must be properly grounded in accordance with all applicable codes. It can be installed in the back wall directly behind the oven. The outlet should be located anywhere within the shaded area.


27-Inch Traditional




30-Inch Traditional









BUILT-IN MICROWAVES

MCES



MCES

SPECIFICATIONS

Overall Microwave Width	23 7 /8"
Overall Microwave Height	14 ¹³ / ₁₆ "
Overall Microwave Depth	19 ⁵ /16"
Cutout Width (27" Trim Kit)	25 7 / ₁₆ "
Cutout Width (30" Trim Kit)	28 7 /16"
Cutout Height	19 7 /8"
Cutout Depth	21"
27" Trim Kit (Overall W x H x D)	26 ³ /4" × 20 ¹ /2" × 1 ¹ /2"
30" Trim Kit (Overall W x H x D)	29 ³ /4" × 20 ¹ /2" × 1 ¹ /2"
Max. Microwave Power	1,000 Watts
Total Watts	1,500
Electrical Supply	120V/60Hz
Required Circuit Breaker	20 Amp
Power Cord Length	41 ⁵ /16"
Power Cord Included	120V-3-Wire
Interior Dimensions (W x H x D)	16 1/4" × 9 1/2" × 16 ¹³ /16"
Shipping Weight (lbs.)	40

MCES

PERFORMANCE

- Automatic Convection Bake programs
- Innovative Microwave Inverter technology offers consistent cooking performance
- 1,000 Watts Microwave power
- 10 Microwave power levels
- Sensor cooking programs measure humidity and adjust cooking level and cooking time
- Popcorn program
- Quick Defrost
- Timer offers automatic delay start mode
- Keep Warm mode
- Quick Minute conveniently adds cooking time
- 1.5 cu. ft. Stainless Steel cavity
 - 15-inch recessed ceramic turntable

DESIGN

- Built-in Convection Microwave is the perfect companion for any Thermador Wall Oven
- Chiseled and bold Thermador design
- Available with 27" or 30" Trim Kit for a sleek built-in look
- Premium glass touch control
- Blue digital display with scrolling text

ACCESSORIES



MCT27JS 27-Inch Trim Kit



MCT30JS 30-Inch Trim Kit

BUILT-IN MICROWAVES CONVECTION

BUILT-IN MICROWAVES

INSTALLATION OPTIONS

WALL-MOUNTED OR CABINET INSTALLATION

A Thermador Microwave may be installed into a cabinet or wall by itself, or above any Thermador Built-in Oven.

A Thermador Microwave may also be installed above any Thermador Warming Drawer.

To reduce the risk of fire and electric shock, install microwave at least $3\!/\!4"$ above designated oven or warming drawer.

IMPORTANT

MCES models must be used in conjunction with a 27-inch or 30-inch microwave trim kit.

MICROWAVE OVEN AND CUTOUT DIMENSIONS

